

# SG-TP03

## Manual Taping Machine



### Features

- ✚ Applicable tape Width: 8mm ~ 80mm
- ✚ Adjustable PSA and HSA sealer assembly
- ✚ PLC controlled seal temperature 0~260°C
- ✚ Continuous speed up to 150mm/sec
- ✚ Feeder tape contains material with  $\Psi$ 200mm ~  $\Psi$ 550mm share type
- ✚ High-brightness LED counter display
- ✚ Carrier tape pitch control 4mm ~ 76mm
- ✚ Friendly software setup and operation
- ✚ Optional CCD and sensor inspection

### Introduction

The new generation taping machine was designed to deliver for small, ultra-thin and variety devices packages. Flexible and easy to operation, to achieve optimized throughput and change over time. Independently controlled temperature, speed and press force to assure the best sealing quality and reliability.

### Options

- CCD Vision Inspection
- Empty Pocket Detector
- Devices Floating Sensor

### Specifications

- N.W.: 26kgs
- G.W.: 56kgs
- Shipping Dimension: 120cmx157cmx75cm
- Power required: 220V/50/60Hz, single
- Air source: 5.0kgf/70psi

System General Ltd Taiwan Branch, 6F., No.205~3, Sec. 3, Beixin Road, Xindian Dist., New Taipei City 231, Taiwan, R.O.C.

Tel: +886-2-8913-1997 email: [info@sg.com.tw](mailto:info@sg.com.tw) URL: [www.sg.com.tw](http://www.sg.com.tw)